

# Enhanced Deep Penetration Flow

Repair from the root, sealing cracks and blocking rainwater.

## 流动性升级 直达缝隙底部

从根本上解决问题，  
胶体流入裂缝根部全面阻止雨水渗透。

Crack sealant flows deep for lasting root-level waterproofing.

灌缝胶能流动裂缝深处，  
真正做到根部持久防水。

Solvent Based



UNICORN  
PAINT

# GROUTFLEX

*Concrete Crack Repair Sealant*





## All New Upgraded Formula Quick Dry in 2 Hours

Enhanced resin formula for durable, high elasticity.

## 全新升级2小时速干 高弹抗裂灌缝胶

升级树脂胶体，高弹性效果更持久



\* The above timings are based on our laboratory tests. Actual drying time may vary depending on temperature and humidity. Please refer to on-site conditions.

\* 以上时间描述为公司实验的实测数据，干燥时间会随着温度和湿度影响变化，具体干燥时间以实际施工环境为准。

# From application to waterproofing in just **2 hours**

Made with high-polymer resin, cures in 2 hours, providing waterproof protection even if it rains.

## 施工到防水，最快只需**两小时**

原材料采用高分子树脂，可以达到两小时固化，快速达到防水性能，不用担心施工后下雨问题。



Apply to moist surfaces 潮湿基面施工



Bubble-free finish 固化完成，拒绝气泡

## Direct application on wet surfaces

Its water-insoluble formula require minimal substrate preparation and applied in rain or on damp surfaces - unlike ordinary materials.

## 潮湿基面可直接施工

本产品有不溶于水的特性，对施工基面要求低，下雨天或潮湿均可施工是普通材料无法比拟的。

\* The above timings are based on our laboratory tests. Actual drying time may vary depending on temperature and humidity. Please refer to on-site conditions.

\* 以上时间描述为公司实验的实测数据，干燥时间会随着温度和湿度影响变化，具体干燥时间以实际施工环境为准。



# Application Instructions 施工说明

- 1

Surface must be clean, free of dust and grease.
- 2

Once opened, use promptly to avoid hardening.
- 3

Curing time may vary with temperature, lower temperatures will extend curing time.
- 4

After sealing, use a spatula to smooth excess gel from the gaps.
- 5

Store in a cool & dry place.

- 1

施工表面必须保持干净，无灰尘和油污等。
- 2

开袋后请尽快使用，避免产品固化影响使用。
- 3

天气温度对固化时间有所影响，环境温度低固化时间变长属于正常现象。
- 4

打胶完成后，需用刮片将溢出缝隙的胶体刮涂平整。
- 5

产品需储存于低温干燥的地方。

# Reference Area 参考面积

<div>M / Pack</div> <div>Crack Width</div> <div>Crack Depth</div>	2MM	3MM	5MM	7MM	9MM	1CM	1.5CM	2CM
2MM	125m	83m	50m	35.7m	27.8m	25m	16.7m	12.5m
5MM	50m	33m	20m	14.3m	11.1m	10m	6.67m	5m
1CM	25m	16.7m	10m	7.14m	5.56m	5m	3.33m	2.5m
1.5CM	16.7m	11.1m	6.67m	4.76m	3.7m	3.33m	2.22m	1.7m
2CM	12.5m	8.33m	5m	3.57m	2.78m	2.5m	1.67m	12.25m

\* The above chart is theoretical if for reference only.  
Actual usage may vary depending on site conditions.

\* 以上表格为理论用量参考，实际施工过程中存在不定因素，具体用量以实际施工为准。





# GROUTFLEX

Concrete Crack Repair Sealant

## 产品规格

Product Specifications

500G

## 储存有效期

Shelf Life

12 Months

## 颜色

Product Colour

Grey

## 配方类别

Product Formulation

High-Polymer Resin Sealant

## 施工方式

Application Method

Crack / Gap / Joint Filling

## 适用季节

Suitable For

All Seasons

## 产品特点

Product Features

Cures In 2 Hours, Bond Firmly

## 适用场景 Scope of Application

Roads, Plazas, Wall Penetrating Pipes, Docks, Roof Cracks, Concrete Structured Basements, Interior Door Frames, Window Sills, Wall Expansion Joints, Cutting Joints and other Seams or Cracks Requiring Filling and Sealing.

## 产品优势，轻松解决问题

## Product Strength: Effortless Problem Solving



持久防水  
Durable Adhesion



高弹抗裂  
High Elasticity & Crack Resistance



施工便捷  
Easy Application



抗冻耐晒  
Weather Resistance



两小时速干  
2-hour Quick Dry



粘接性强  
Superior Adhesion

Imported By: Unicorn Marketing Sdn Bhd (1302862-V)

No. 9 & 11, Jalan Makmur, Taman Perindustrian Maju Cemerlang, 81800 Ulu Tiram, Johor, Malaysia.

Tel: (+6) 07-288 2233 Fax: (+6) 07-861 1726 Email: sales@unicorncoating.com.my Website: www.unicorncoating.com.my