



## **MATT FINISH (Interior)**

# **EAZY-TECH MATT EMULSION**

TDS 2.0007  
Established: Dec 2025  
Updated: NA

### **Product Description / Uses**

**EAZY-TECH Luxury Matt Emulsion** is a styrene acrylic emulsion paint with non-added lead and mercury which gives a very smooth matt finishing for internal walls. It is specially formulated with low VOC and alkyd phenol ethoxylate free. It also does not intentionally contain formaldehyde substances. This affordable matt emulsion has good hiding power, good coverage, easy application, good durability, fungus resistance and washability.

### **Physical Characteristics**

Ingredient	Acrylic copolymer emulsion, pigments, extenders and additives
Non-Volatile	~ 50 %
Density	1.20 – 1.40 (kg/litre)
Viscosity	100 – 110 Krebs Unit
Theoretical Coverage	10 – 12 m <sup>2</sup> / litre / coat
Gloss	Matt

### **Properties**

Recommended DFT	30 µm per coat
Drying Time :	
Touch dry	≤ 15 minutes
Hard dry	≤ 1 hours
Recoating	2 hours
Recommended Painting System	1 coat of Unicorn Seal-Tech Wall Sealer 2 coats of Unicorn Eazy-Tech Luxury Matt Emulsion

### **Surfaces Preparation**

Surfaces must be sound, dry, clean and free from any foreign matters before painting. The old chalky surface and flaking paint must be properly sanded down/scrubbed and cleaned with water. Besides, the moisture content of the substrate must be ≤ 14% before commencement of the painting job.

The hairline cracks must be properly filled up with suitable putty or filler. Any fungus and/or algae affected area must be properly treated before painting.

### **Application Method**

Brush, roller or airless spray

The product is supplied ready for use after ***stir homogenously***.

If thinning is required, please refer to the recommended dilution as per below.

For brushing / rolling : ≤ 5% of clean water.

For spraying : ≤ 10% of clean water.

TDS 2.0007 (R00)